

Werkstoff:
 E-CU sn = Elektrolytkupfer verzinkt

Matière:
 E-CU sn = cuivre électrolytique étamé

Material:
 E-CU sn = tin-plated electrolytic copper

Temperaturbeständigkeit:
 bis + 125°C

Résistant à une température:
 jusqu'à + 125°C


Temperature range:
 up to + 125°C

UL-No. E235797

mm ²	AWG	für Bolzen pour borne for stud mm	Artikelnummer Numéro d'article Part-No.	DIN	øD mm	øD1 mm	øD3 mm	L mm	A mm	R mm	S mm	Werkzeuge Outils Toolings
0.25-0.5	24-22	M2	3490a	2-0.5	2.2	1	5	10	4	4	0.5	3975d
	24-22	M2.5	3491a	2.5-0.5	2.7	1	5	10	4	4	0.5	
	24-22	M3	3492a	3-0.5	3.2	1	5	10	4	4.5	0.5	
	24-22	M3.5	3493a	3.5-0.5	3.7	1	6	12	4	4.5	0.5	
	24-22	M4	3494a	4-0.5	4.3	1	6.5	12	4	6	0.5	
	24-22	M5	3496a	5-0.5	5.3	1	8	12	4	6.5	0.5	
0.5-1	22-18	M2	3500a	*	2.2	1.6	6	11	5	4.5	0.8	3975d, 3980n, 3983p.2, 3984e
	22-18	M2.5	3501a	2,5-1	2.7	1.6	6	11	5	4	0.8	
	22-18	M3	3502a	3.0-1	3.2	1.6	6	11	5	4.5	0.8	
	22-18	M3	3503a	*	3.2	1.6	5.5	10	4.8	3.5	0.8	
	22-18	M3.5	3504a	3,5-1	3.7	1.6	6	11	5	4.5	0.8	
	22-18	M3.5	3505a	*	3.7	1.6	6.5	11	4.8	3.5	0.8	
	22-18	M4	3506a	*	4.3	1.6	6.5	11	4.8	3.5	0.8	
	22-18	M4	3507a	*	4.3	1.6	7	11.5	5	5.5	0.8	
	22-18	M4	3508a	4.0-1	4.3	1.6	8	12	5	6	0.8	
	22-18	M5	3509a	*	5.3	1.6	8	12.5	5	6	0.8	
	22-18	M5	3510a	5.0-1	5.3	1.6	10	13	5	6.5	0.8	
	22-18	M6	3512a	*	6.4	1.6	10	13	5	6.5	0.8	
	22-18	M6	3513a	*	6.4	1.6	11	15	5	10	0.8	
	22-18	M8	3514a	*	8.4	1.6	14	17	5	10	0.8	
1.5-2.5	16-14	M3	3515a	3-2,5	3.2	2.3	6	11	5	4.5	0.8	3975d, 3980n, 3983p.2, 3984e
	16-14	M3.5	3516a	3.5-2.5	3.7	2.3	6	11	5	4.5	0.8	
	16-14	M3.5	3517a	*	3.7	2.3	6.6	11	5	4.5	0.8	
	16-14	M4	3518a	*	4.3	2.3	6.8	11.6	5	4.5	0.8	
	16-14	M4	3519a	4-2,5	4.3	2.3	8	12	5	6	0.8	
	16-14	M5	3520a	*	5.3	2.3	8	13.5	5	6	0.8	
	16-14	M5	3521a	5-2,5	5.3	2.3	10	14	5	6.5	0.8	
	16-14	M6	3522a	*	6.4	2.3	12	16	5	6.5	0.8	
	16-14	M6	3523a	6-2,5	6.5	2.3	11	16	5	7.5	0.8	
	16-14	M8	3525a	8-2,5	8.4	2.3	14	17	5	10	0.8	
	16-14	M8	3525a.42	8-2,5	8.4	2.3	14	17	5	10	0.8	
	16-14	M10	3527a	*	10.5	2.3	18	18.5	5	12	0.8	
	16-14	M12	3528a	*	13	2.3	18	20	5	12	0.8	
	16-14	M16	3529a	*	17.2	2.3	27	26	5	16	0.8	
4-6	12-10	M4	3530a	4-6	4.3	3.6	8	14	6	6	1	3980n, 3984f
	12-10	M5	3532a	5-6	5.3	3.6	10	15	6	6.5	1	
	12-10	M6	3534a	6-6	6.5	3.6	11	16	6	7.5	1	
	12-10	M8	3538a	8-6	8.4	3.6	14	19	6	10	1	
	12-10	M10	3540a	10-6	10.5	3.6	18	21	6	12	1	
	12-10	M12	3542a	*	13	3.6	18	21	6	18	1	

UL-No. E235797

mm ²	AWG	für Bolzen pour borne for stud mm	Artikelnummer Numéro d'article Part-No.	DIN	øD mm	øD1 mm	øD3 mm	L mm	A mm	R mm	S mm	Werkzeuge Outils Toolings
10	8	M4	3544a	*	4.3	4.5	12	18	8	6.5	1.2	3980p, 3981an, 3982cn
	8	M5	3547a	5-10	5.3	4.5	10	16	8	6.5	1.1	
	8	M6	3549a	6-10	6.5	4.5	11	17	8	7.5	1.1	
	8	M8	3551a	8-10	8.4	4.5	14	20	8	10	1.1	
	8	M10	3553a	10-10	10.5	4.5	18	21	8	12	1.1	
	8	M12	3555a	12-10	13	4.5	22	23	8	13	1.1	
16	6	M4	3559a	4-16	4.3	5.8	11	20	10	7.5	1.2	3980p, 3981an, 3982cn
	6	M5	3560a	5-16	5.3	5.8	11	20	10	7.5	1.2	
	6	M6	3562a	6-16	6.5	5.8	11	20	10	7.5	1.2	
	6	M8	3564a	8-16	8.4	5.8	14	22	10	10	1.2	
	6	M10	3566a	10-16	10.5	5.8	18	24	10	12	1.2	
	6	M12	3568a	12-16	13	5.8	22	26	10	13	1.2	
25	4	M5	3571a	5-25	5.3	7.5	12	25	11	7.5	1.5	3980p, 3981an, 3982cn, 3982g
	4	M6	3573a	6-25	6.5	7.5	12	25	11	7.5	1.5	
	4	M8	3575a	8-25	8.4	7.5	16	25	11	10	1.5	
	4	M10	3577a	10-25	10.5	7.5	18	26	11	12	1.5	
	4	M12	3579a	12-25	13	7.5	22	31	11	13	1.5	
	4	M16	3580a	16-25	17	7.5	28	35	11	16	1.5	
35	2	M6	3582a	6-35	6.5	9	15	26	12	9.5	1.6	3981an, 3982cn, 3982g
	2	M8	3584a	8-35	8.4	9	16	26	12	10	1.6	
	2	M10	3586a	10-35	10.5	9	18	27	12	12	1.6	
	2	M16	35881a	16-35	17	9	28	36	12	16	1.6	
	2	M12	3588a	12-35	13	9	22	31	12	13	1.6	
50	1/0	M6	3589a	6-50	6.5	11	18	34	16	10	1.8	3981an, 3982cn, 3982g
	1/0	M8	3590a	8-50	8.4	11	18	34	16	10	1.8	
	1/0	M10	3592a	10-50	10.5	11	18	34	16	12	1.8	
	1/0	M12	3593a	12-50	13	11	22	36	16	13	1.8	
	1/0	M16	3594a	16-50	17	11	28	40	16	16	1.8	
70	2/0	M6	359400a	6-70	6.5	13	22	38	18	12	2	3981an, 3982cn, 3982g
	2/0	M8	359401a	8-70	8.4	13	22	38	18	12	2	
	2/0	M10	359402a	10-70	10.5	13	22	38	18	12	2	
	2/0	M12	359403a	12-70	13	13	22	38	18	13	2	
	2/0	M16	359404a	16-70	17	13	28	42	18	16	2	
95	3/0	M8	359404b	8-95	8.4	15	24	42	20	12	2.5	3982cn
	3/0	M10	359405a	10-95	10.5	15	24	42	20	12	2.5	
	3/0	M12	359406a	12-95	13	15	24	42	20	13	2.5	
	3/0	M16	359407a	16-95	17	15	28	44	20	16	2.5	
120	250 MCM	M10	359408a	10-120	10.5	16.5	24	44	22	12	3	3982cn
	250 MCM	M12	359409a	12-120	13	16.5	24	44	22	13	3	
	250 MCM	M16	359410a	16-120	17	16.5	28	48	22	16	3	
150	300 MCM	M12	359411a	12-150	13	19	30	50	24	13	3.2	3982cn
	300 MCM	M16	359412a	16-150	17	19	30	50	24	16	3.2	
185	350 MCM	M12	359413a	12-185	13	21	36	50	28	16	3.5	3982cn
	350 MCM	M16	359414a	16-185	17	21	36	50	28	16	3.5	
240	500 MCM	M12	359415a	12-240	13	23.5	38	56	32	16	4	3982cn
	500 MCM	M16	359416a	16-240	17	23.5	38	56	32	16	4	



Werkstoff:
 E-CU sn = Elektrolytkupfer verzinkt

Matière:
 E-CU sn = cuivre électrolytique étamé

Material:
 E-CU sn = tin-plated electrolytic copper

Temperaturbeständigkeit:
 bis + 125°C

Résistant à une température:
 jusqu'à + 125°C

Temperature range:
 up to + 125°C

UL-No. E235797

mm ²	AWG	für Bolzen pour borne for stud mm	Artikelnummer Numéro d'article Part-No.	DIN	øD mm	øD1 mm	øD3 mm	L mm	A mm	R mm	S mm	Werkzeuge Outils Toolings
0.25-0.5	24-22	M3	3492c	*	3.2	1	5	8	4	3.5	0.5	3975d
0.5-1	22-18	M3	3502c	*	3.2	1.6	6	11	5	4.5	0.8	3975d, 3980n, 3983p.2, 3984e
	22-18	M3	3503c	*	3.2	1.6	6.5	8	4	3.5	0.8	
	22-18	M3.5	3504c	*	3.7	1.6	6	11	5	4.5	0.8	
	22-18	M4	3507c	*	4.3	1.6	6.8	12	5	5.5	0.8	
	22-18	M4	3508c	*	4.3	1.6	8	12	5	6	0.8	
	22-18	M5	3510c	*	5.3	1.6	10	13	5	6.5	0.8	
	22-18	M6	3513c	*	6.5	1.6	11	15	5	10	0.8	
	22-18	M8	3514c	*	8.5	1.6	12	17	5	10	0.8	
1.5-2.5	16-14	M3	3515c	*	3.2	2.3	5.5	13	5	4.5	0.8	
	16-14	M3.5	3517c	*	3.7	2.3	6	11	5	4.5	0.8	
	16-14	M4	3518c	*	4.3	2.3	6.8	11.7	5	4.5	0.8	
	16-14	M4	3519c	*	4.3	2.3	8	12	5	6	0.8	
	16-14	M5	3521c	*	5.3	2.3	10	14	5	6.5	0.8	
	16-14	M6	3523c	*	6.5	2.3	11	16	5	7.5	0.8	
4-6	12-10	M4	3530c	*	4.3	3.6	8	14	6	6	1	
	12-10	M5	3532c	*	5.3	3.6	10	15	6	6.5	1	
	12-10	M6	3534c	*	6.5	3.6	11	16	6	7.5	1	
	12-10	M8	3538c	*	8.5	3.6	14	19	6	10	1	
10	8	M5	3547c	*	5.3	4.5	10.5	16.5	8.5	-	1.2	3980p, 3981an, 3982cn
	8	M6	3549c	*	6.5	4.5	10.8	17	8.5	-	1.2	
16	6	M6	3562c	*	6.4	5.8	11	21	10.5	-	1.5	
	6	M8	3564c	*	8.4	5.8	13.8	21	10.5	-	1.5	