

Werkstoff/Matière/Material
.4 = Kupfer/cuivre/copper

█ = Oberflächen/Surface/Surface-plating
Seite/page/page 5.011



mm ²	AWG	Artikelnummer Numéro d'article Part-No.	DIN	øD1 mm	øD2 mm	L1 mm	S mm	Werkzeuge Outils Toolings
0.1-0.3	26-24	440005.4	*	0.7	1.7	5	0.15	3984h, 4517, 4536, 4542
	26-24	440007.4	*	0.7	1.7	7	0.15	
	26-24	440010.4	*	0.7	1.7	10	0.15	
	26-24	440015.4	*	0.7	1.7	15	0.15	
0.34	24	449905.4	*	0.9	1.8	5	0.15	
	24	449907.4	*	0.9	1.8	7	0.15	
0.5	22-20	440106.4	0.5-6	1	2.1	6	0.15	
	22-20	440108.4	*	1	2.1	8	0.15	
	22-20	440110.4	0.5-10	1	2.1	10	0.15	
	22-20	440112.4	*	1	2.1	12	0.15	
	22-20	440130.4	*	1	2.1	30	0.15	
0.75	20-18	440206.4	0.75-6	1.2	2.3	6	0.15	
	20-18	440208.4	*	1.2	2.3	8	0.15	
	20-18	440210.4	0.75-10	1.2	2.3	10	0.15	
	20-18	440212.4	*	1.2	2.3	12	0.15	
	20-18	440220.4	*	1.2	2.3	20	0.15	
1	18	440306.4	1-6	1.4	2.5	6	0.15	
	18	440308.4	*	1.4	2.5	8	0.15	
	18	440310.4	1-10	1.4	2.5	10	0.15	
	18	440312.4	*	1.4	2.5	12	0.15	
	18	440320.4	*	1.4	2.5	20	0.15	
1.5	16	440406.4	*	1.7	2.8	6	0.15	
	16	440407.4	1.5-7	1.7	2.8	7	0.15	
	16	440408.4	*	1.7	2.8	8	0.15	
	16	440410.4	1.5-10	1.7	2.8	10	0.15	
	16	440412.4	1.5-12	1.7	2.8	12	0.15	
	16	440415.4	*	1.7	2.8	15	0.15	
	16	440418.4	1.5-18	1.7	2.8	18	0.15	
16	440420.4	*	1.7	2.8	20	0.15		
2.5	14	440505.4	*	2.2	3.4	5	0.15	
	14	440506.4	*	2.2	3.4	6	0.15	
	14	440507.4	2.5-7	2.2	3.4	7	0.15	
	14	440508.4	*	2.2	3.4	8	0.15	
	14	440510.4	2.5-10	2.2	3.4	10	0.15	
	14	440512.4	2.5-12	2.2	3.4	12	0.15	
	14	440515.4	*	2.2	3.4	15	0.15	
	14	440518.4	2.5-18	2.2	3.4	18	0.15	
	14	440520.4	*	2.2	3.4	20	0.15	
	14	440530.4	*	2.2	3.4	30	0.15	
4	12	440608.4	*	2.8	4	8	0.2	
	12	440609.4	4-9	2.8	4	9	0.2	
	12	440610.4	*	2.8	4	10	0.2	
	12	440612.4	4-12	2.8	4	12	0.2	
	12	440615.4	4-15	2.8	4	15	0.2	
	12	440618.4	4-18	2.8	4	18	0.2	
	12	440620.4	*	2.8	4	20	0.2	
	12	440630.4	*	2.8	4	30	0.2	
120	4/0	441532.4	*	16.5	19	32	0.5	
150	250MCM	441632.4	*	18.5	21	32	0.5	
6	10	440704.4	*	3.5	4.7	4	0.2	
	10	440706.4	*	3.5	4.7	6	0.2	
	10	440710.4	6-10	3.5	4.7	10	0.2	
	10	440712.4	6-12	3.5	4.7	12	0.2	
	10	440715.4	6-15	3.5	4.7	15	0.2	
	10	440718.4	6-18	3.5	4.7	18	0.2	
	10	440720.4	*	3.5	4.7	20	0.2	
	10	440725.4	*	3.5	4.7	25	0.2	
	10	440730.4	*	3.5	4.7	30	0.2	
	10	8	440812.4	10-12	4.5	5.8	12	0.2
8		440815.4	10-15	4.5	5.8	15	0.2	
8		440816.4	*	4.5	5.8	16	0.2	
8		440818.4	10-18	4.5	5.8	18	0.2	
8		440820.4	*	4.5	5.8	20	0.2	
8	440825.4	*	4.5	5.8	25	0.2		
16	6	440912.4	16-12	5.8	7.5	12	0.2	
	6	440915.4	16-15	5.8	7.5	15	0.2	
	6	440918.4	16-18	5.8	7.5	18	0.2	
	6	440920.4	*	5.8	7.5	20	0.2	
	6	440922.4	*	5.8	7.5	22	0.2	
	6	440925.4	16-25	5.8	7.5	25	0.2	
	6	440930.4	*	5.8	7.5	30	0.2	
6	440932.4	16-32	5.8	7.5	32	0.2		
25	4	441012.4	*	7.3	9.5	12	0.2	
	4	441015.4	25-15	7.3	9.5	15	0.2	
	4	441018.4	25-18	7.3	9.5	18	0.2	
	4	441020.4	*	7.3	9.5	20	0.2	
	4	441025.4	25-25	7.3	9.5	25	0.2	
	4	441028.4	*	7.3	9.5	28	0.2	
	4	441032.4	25-32	7.3	9.5	32	0.2	
35	2	441112.4	*	8.3	11	12	0.2	
	2	441115.4	*	8.3	11	15	0.2	
	2	441118.4	35-18	8.3	11	18	0.2	
	2	441120.4	*	8.3	11	20	0.2	
	2	441125.4	35-25	8.3	11	25	0.2	
	2	441130.4	*	8.3	11	30	0.2	
	2	441132.4	35-32	8.3	11	32	0.2	
50	1/0	441218.4	50-18	10.3	13	18	0.3	
	1/0	441220.4	*	10.3	13	20	0.3	
	1/0	441222.4	*	10.3	13	22	0.3	
	1/0	441225.4	50-25	10.3	13	25	0.3	
	1/0	441230.4	*	10.3	13	30	0.3	
	1/0	441232.4	50-32	10.3	13	32	0.3	
1/0	441240.4	*	10.3	13	40	0.3		
70	2/0	441322.4	*	12.5	15	22	0.4	
	2/0	441325.4	*	12.5	15	25	0.4	
	2/0	441332.4	*	12.5	15	32	0.4	
95	3/0	441420.4	*	14.5	17	20	0.4	
	3/0	441425.4	*	14.5	17	25	0.4	
	3/0	441432.4	*	14.5	17	32	0.4	


Messing-Aderendhülsen ohne Isolation

Embouts de fil en laiton sans isolation

Uninsulated brass ferrules

Werkstoff/Matière/Material
.6 = Messing/laiton/brass

■ = Oberflächen/Surface/Surface-plating
Seite/page/page 5.011




mm ²	AWG	Artikelnummer Numéro d'article Part-No.	øD1 mm	øD2 mm	L1 mm	S mm	Werkzeuge Outils Toolings		
0.1-0.3	26-24	450006.6	0.7	1.8	6	0.2	3984h, 4517, 4536, 4542		
	26-24	450008.6	0.7	1.8	8	0.2			
	26-24	450012.6	0.7	1.8	12	0.2			
0.5	22-20	450104.6	1.1	2.2	4	0.2	3983p.3, 3984h, 4518n, 4523n, 4527, 4531, 4536, 4542		
	22-20	450106.6	1.1	2.2	6	0.2			
	22-20	450107.6	1.1	2.2	7	0.2			
	22-20	450108.6	1.1	2.2	8	0.2			
	22-20	450110.6	1.1	2.2	10	0.2			
	22-20	450112.6	1.1	2.2	12	0.2			
	22-20	450115.6	1.1	2.2	15	0.2			
	22-20	450118.6	1.1	2.2	18	0.2			
0.75	20-18	450206.6	1.3	2.5	6	0.2			
	20-18	450207.6	1.3	2.5	7	0.2			
	20-18	450208.6	1.3	2.5	8	0.2			
	20-18	450210.6	1.3	2.5	10	0.2			
	20-18	450212.6	1.3	2.5	12	0.2			
	20-18	450215.6	1.3	2.5	15	0.2			
	20-18	450220.6	1.3	2.5	20	0.2			
	1	18	450306.6	1.5	2.7	6		0.2	3983p.3, 3984h, 4518n, 4521, 4523n, 4527, 4531, 4536, 4542
18		450307.6	1.5	2.7	7	0.2			
18		450308.6	1.5	2.7	8	0.2			
18		450309.6	1.5	2.7	9	0.2			
18		450310.6	1.5	2.7	10	0.2			
18		450312.6	1.5	2.7	12	0.2			
18		450315.6	1.5	2.7	15	0.2			
18		450320.6	1.5	2.7	20	0.2			
1.5	16	450406.6	1.8	3	6	0.2	3984j, 4521, 4523n, 4531, 4536, 4542		
	16	450407.6	1.8	3	7	0.2			
	16	450408.6	1.8	3	8	0.2			
	16	450410.6	1.8	3	10	0.2			
	16	450412.6	1.8	3	12	0.2			
	16	450415.6	1.8	3	15	0.2			
	16	450420.6	1.8	3	20	0.2			
	2.5	14	450505.6	2.2	3.5	5		0.2	3983p.3, 3984j, 4521, 4522, 4526n
14		450506.6	2.2	3.5	6	0.2			
14		450507.6	2.2	3.5	7	0.2			
14		450508.6	2.2	3.5	8	0.2			
14		450510.6	2.2	3.5	10	0.2			
14		450512.6	2.2	3.5	12	0.2			
14		450515.6	2.2	3.5	15	0.2			
14		450520.6	2.2	3.5	20	0.2			
14		450530.6	2.2	3.5	30	0.2			
2.75		14	4505b05.6	2.6	3.8	5	0.2	3983p.3, 3984h, 4521, 4523n, 4531, 4536, 4542	
		14	4505b08.6	2.6	3.8	8	0.2		
		14	4505b10.6	2.6	3.8	10	0.2		
		14	4505b12.6	2.6	3.8	12	0.2		
		14	4505b20.6	2.6	3.8	20	0.2		
	4 Seil	12	4506a06.6	2.8	4	6	0.2		3983p.3, 3984h, 4521, 4523n, 4531, 4536, 4542
		12	4506a08.6	2.8	4	8	0.2		
		12	4506a10.6	2.8	4	10	0.2		
		12	4506a12.6	2.8	4	12	0.2		
		12	4506a15.6	2.8	4	15	0.2		
		12	4506a20.6	2.8	4	20	0.2		
		12	4506a30.6	2.8	4	30	0.2		
4 Litze		12	4506b06.6	3	4.3	6	0.25	3983p.3, 3984j, 4521, 4523n, 4526n, 4531, 4536, 4542	
	12	4506b08.6	3	4.3	8	0.25			
	12	4506b10.6	3	4.3	10	0.25			
	12	4506b11.6	3	4.3	11	0.25			
	12	4506b12.6	3	4.3	12	0.25			
	12	4506b15.6	3	4.3	15	0.25			
	12	4506b20.6	3	4.3	20	0.25			
	6 Seil	10	4507a06.6	3.6	5	6	0.2		3983p.3, 3984j, 4521, 4523n, 4526n, 4531, 4536, 4542
10		4507a08.6	3.6	5	8	0.2			
10		4507a10.6	3.6	5	10	0.2			
10		4507a12.6	3.6	5	12	0.2			
10		4507a15.6	3.6	5	15	0.2			
10		4507a20.6	3.6	5	20	0.2			
6 Litze	10	4507b04.6	4	5.5	4	0.25	3984j, 4521, 4523n, 4531, 4542		
	10	4507b06.6	4	5.5	6	0.25			
	10	4507b08.6	4	5.5	8	0.25			
	10	4507b10.6	4	5.5	10	0.25			
	10	4507b12.6	4	5.5	12	0.25			
	10	4507b15.6	4	5.5	15	0.25			
	10	4507b20.6	4	5.5	20	0.25			
	10	4507b30.6	4	5.5	30	0.25			
10 Seil	8	4508a06.6	4.5	6	6	0.25	3983p.3, 3984j, 4521, 4522, 4526n		
	8	4508a08.6	4.5	6	8	0.25			
	8	4508a12.6	4.5	6	12	0.25			
	8	4508a15.6	4.5	6	15	0.25			
	8	4508a20.6	4.5	6	20	0.25			
	8	4508a30.6	4.5	6	30	0.25			
10 Litze	8	4508b06.6	5	6.5	6	0.25	3983p.3, 3984j, 4521, 4522, 4526n		
	8	4508b08.6	5	6.5	8	0.25			
	8	4508b12.6	5	6.5	12	0.25			
	8	4508b15.6	5	6.5	15	0.25			
	8	4508b18.6	5	6.5	18	0.25			
	8	4508b20.6	5	6.5	20	0.25			
	8	4508b30.6	5	6.5	30	0.25			

Messing-Aderendhülsen ohne Isolation Embouts de fil en laiton sans isolation Uninsulated brass ferrules

Werkstoff/Matière/Material
.6 = Messing/laiton/brass

■ = Oberflächen/Surface/Surface-plating
Seite/page/page 5.011



mm ²	AWG	Artikelnummer Numéro d'article Part-No.	øD1 mm	øD2 mm	L1 mm	S mm	Werkzeuge Outils Toolings	
16 Seil	6	4509a06.6 ■	5.5	7	6	0.25	3984j, 4522, 4526n	
	6	4509a08.6 ■	5.5	7	8	0.25		
	6	4509a12.6 ■	5.5	7	12	0.25		
	6	4509a15.6 ■	5.5	7	15	0.25		
	6	4509a20.6 ■	5.5	7	20	0.25		
	6	4509a30.6 ■	5.5	7	30	0.25		
	6	4509a40.6 ■	5.5	7	40	0.25		
16 Litze	6	4509b06.6 ■	6.4	8	6	0.3		
	6	4509b08.6 ■	6.4	8	8	0.3		
	6	4509b12.6 ■	6.4	8	12	0.3		
	6	4509b15.6 ■	6.4	8	15	0.3		
	6	4509b20.6 ■	6.4	8	20	0.3		
	6	4509b30.6 ■	6.4	8	30	0.3		
	6	4509b40.6 ■	6.4	8	40	0.3		
25 Seil	4	4510a12.6 ■	7	8.8	12	0.25	4522, 4538n, 4539n	
	4	4510a15.6 ■	7	8.8	15	0.25		
	4	4510a18.6 ■	7	8.8	18	0.25		
	4	4510a20.6 ■	7	8.8	20	0.25		
	4	4510a40.6 ■	7	8.8	40	0.25		
25 Litze	4	4510b08.6 ■	7.6	9.5	8	0.2		
	4	4510b12.6 ■	7.6	9.5	12	0.2		
	4	4510b15.6 ■	7.6	9.5	15	0.2		
	4	4510b18.6 ■	7.6	9.5	18	0.2		
	4	4510b20.6 ■	7.6	9.5	20	0.2		
	4	4510b30.6 ■	7.6	9.5	30	0.2		
35 Seil	2	451120.6 ■	8	10.5	20	0.5	4522, 4538n	
	2	451130.6 ■	8	10.5	30	0.5		
35 Litze	2	451215.6 ■	9.4	11.5	15	0.3		
	50 Seil	1/0	451218.6 ■	9.4	11.5	18		0.3
		2		9.4	11.5	20		0.3
	1/0	451220.6 ■	9.4	11.5	20	0.3		
	2	451230.6 ■	9.4	11.5	30	0.3		
	1/0							
2								
50 Litze	1/0	451320.6 ■	11	13.5	20	0.5		4537, 4539n
	70 Seil	2/0	451322.6 ■	11	13.5	22	0.5	
		1/0		11	13.5	20	0.5	
	2/0	451330.6 ■	11	13.5	30	0.5		
	1/0							
2/0								
70 Litze	2/0	451420.6 ■	13	15.5	20	0.5	4537	
	95 Seil	3/0	451426.6 ■	13	15.5	26		0.5
		2/0		13	15.5	20		0.5
	3/0	451430.6 ■	13	15.5	30	0.5		
	2/0							
3/0								
95 Litze	4/0	451520.6 ■	15	17.5	20	0.5		
	250 MCM	451530.6 ■	15	17.5	30	0.5		
120 Seil	4/0							
	250 MCM							
120 Litze	250 MCM	451620.6 ■	17	19.5	20	0.5		
	300 MCM							
	250 MCM	451630.6 ■	17	19.5	30	0.5		
150 Seil	250 MCM							
	300 MCM							