

**Bandform**

Werkstoff:  
E-CU sn = Elektrolytkupfer verzinkt

Temperaturbeständigkeit:  
bis +105°C

**en bande**

















Matière:  
E-CU sn = cuivre électrolytique étamé

Résistant à une température:  
jusqu'à +105°C

**chain form**

Material:  
E-CU sn = tin-plated electrolytic copper

Temperature range:  
up to +105°C

mm <sup>2</sup>	AWG	Farben D Couleurs D Colours D	Art.-No. D	Farben F Couleurs F Colours F	Art.-No. F	Farben DIN Couleurs DIN Colours DIN	Art.-No. DIN	øD1 mm	øD2 mm	L1 mm	L2 mm	S1 mm	Werkzeuge Outils Toolings
0.34	24		459908.05000					0.8	2	13	8	0.15	
0.5	22-20		460108.05000		470108.05000		470108.05000	1	2.6	14	8	0.15	4548
0.75	20-18		460208.05000		470208.05000		490208.05000	1.2	2.8	14	8	0.15	
1	18		460308.05000		470308.05000		470308.05000	1.4	3	14	8	0.15	4000, 4000p.6, 4548
1.5	16		460408.05000		470408.05000		470408.05000	1.7	3.5	14	8	0.15	4000, 4000p.7, 4548
2.5	14		460508.03000		470508.03000		460508.03000	2.2	4.2	14	8	0.15	4000, 4000p.8, 4548

**Universal-Anschlagmaschine**

für Aderendhülsen mit Isolation  
in Bandform

**Machine universelle à dénuder et à sertir**

pour embouts de fils pré-isolés  
sur bande

**Universal stripper-crimper**

for pre-insulated endsleeves  
in chain form

0,5-2,5 mm<sup>2</sup>  
(AWG 22-14)

Artikel-Nr.  
Numéro d'article  
Part.-No.

**4548**

