

Rundstecker isoliert Prises cylindriques isol. Pin connectors insulated

UL-No. E330536 mit Stützhülse

Werkstoff:
MS sn = Messing verzinkt

Temperaturbeständigkeit:
PVC -10°C bis +50°C

Strombelastbarkeit:
0.5 – 1.0 mm²/10A max.
1.5 – 2.5 mm²/15A max.
4.0 – 6.0 mm²/25A max.

avec douille-support

Matière:
MS sn = laiton étamé

Résistant à une température de:
PVC -10°C à +50°C



Intensité admissible:
0.5 – 1.0 mm²/10A max.
1.5 – 2.5 mm²/15A max.
4.0 – 6.0 mm²/25A max.




with extra support-sleeve




Material:
MS sn = tin-plated brass

Temperature range:
PVC -10°C up to +50°C

Current carrying capacity:
0.5 – 1.0 mm²/10A max.
1.5 – 2.5 mm²/15A max.
4.0 – 6.0 mm²/25A max.



PVC							
mm ²	AWG	für Stecker pour fiche for plug	Farbe Couleur Colour	Artikelnummer Numéro d'article Part-No.	L mm	øD mm	Werkzeuge Outils Toolings
0.5-1	22-18	Ø 4.0 mm		3915	23	1.7	3974n, 3986c, 3986n, 3986s
1.5-2.5	16-14	Ø 5.0 mm		3916	23	2.3	
4-6	12-10	Ø 5.0 mm		3917	25	3.4	

PVC							
mm ²	AWG	für Stecker pour fiche for plug	Farbe Couleur Colour	Artikelnummer Numéro d'article Part-No.	L mm	øD mm	Werkzeuge Outils Toolings
0.5-1	22-18	Ø 4.0 mm		3920	21.5	1.7	3974n, 3986c, 3986n, 3986s
1.5-2.5	16-14	Ø 5.0 mm		3921	21.5	2.3	
4-6	12-10	Ø 5.0 mm		3922	24	3.4	

Rundstecker isoliert Prises cylindriques isol. Pin connectors insulated

UL-No. E330536 ohne Stützhülse

Werkstoff:
MS sn = Messing verzinkt

Temperaturbeständigkeit:
PVC -10°C bis +50°C

Strombelastbarkeit:
0.5 – 1.0 mm²/10A max.
1.5 – 2.5 mm²/15A max.
4.0 – 6.0 mm²/25A max.

sans douille-support

Matière:
MS sn = laiton étamé

Résistant à une température de:
PVC -10°C à +50°C


Intensité admissible:
0.5 – 1.0 mm²/10A max.
1.5 – 2.5 mm²/15A max.
4.0 – 6.0 mm²/25A max.




without extra support-sleeve


Material:
MS sn = tin-plated brass




Temperature range:
PVC -10°C up to +50°C

Current carrying capacity:
0.5 – 1.0 mm²/10A max.
1.5 – 2.5 mm²/15A max.
4.0 – 6.0 mm²/25A max.



PVC							
mm ²	AWG	für Stecker pour fiche for plug	Farbe Couleur Colour	Artikelnummer Numéro d'article Part-No.	L mm	øD mm	Werkzeuge Outils Toolings
0.5-1	22-18	Ø 4.0 mm		3915s	23	1.7	3974n, 3986c, 3986n, 3986s
1.5-2.5	16-14	Ø 5.0 mm		3916s	24.5	2.3	
4-6	12-10	Ø 5.0 mm		3917s	24	3.4	



PVC							
mm ²	AWG	für Stecker pour fiche for plug	Farbe Couleur Colour	Artikelnummer Numéro d'article Part-No.	L mm	øD mm	Werkzeuge Outils Toolings
0.5-1	22-18	Ø 4.0 mm		3920s	21.5	1.7	3974n, 3986c, 3986n, 3986s
1.5-2.5	16-14	Ø 5.0 mm		3921s	21.5	2.3	
4-6	12-10	Ø 5.0 mm		3922s	24	3.4	