










Junction system Type S, M, L Overview

Suitabel series	Input	Output	Suitabel series
 <p>VSS - Series Type: S, M, L</p>	<p>1, 2</p> <p>Type S</p> 	<p>1, 2</p>	 <p>M8 - Series Type: S, M, L</p>
 <p>DT - Series Type: S, M, L</p>	<p>1, 2, 3</p> <p>Type M</p> 	<p>1, 2, 3</p>	 <p>M12 - Series Type: S, M, L</p>
 <p>ISOBUS - Series Type: L</p>	<p>1 (ISOBUS)</p> <p>Type L</p> 	<p>3, 4</p>	 <p>D-SUB - Series Type: S, M, L</p>

Characteristics	Type S	Type M	Type L
Dimensions (L x W x H mm)	66 x 30 x 15	66 x 40 x 15	76 x 55 x 22
Cable entry	1, 2	1, 2, 3	1
Cable exit	1, 2	1, 2, 3	3, 4
Overmould	TPU UL94 V-0	TPU UL94 V-0	TPU UL94 V-0
Cable quality	PUR (0.75 mm ²)*	PUR (0.75 mm ²)*	PUR (Hybrid)*
Max. cable diameter entry	8 mm	8 mm	17 mm
Max. cable diameter exit	8 mm	8 mm	13 mm (3 exits) 8 mm (4 exits)
Degree of protection	IP67	IP67	IP67

* Other cable qualities on request